

MM

MAJOR & MAKER

					
	Major&Maker Smaragd 200A	Major&Maker Diamond 200B	Major&Maker Sapphire 270B	Major&Maker Crystal 290A	Major&Maker Rubine 290B
Rear washing (spot water jet)	•	•	•	•	•
Front washing (diffused water jet)	•	•	•	•	•
Washing in a mobile mode (massage)	•	•	•	•	•
Intensive washing (Enema)	•	•	•	•	•
Antibacterial washing nozzle	stainless steel	stainless steel	stainless steel	stainless steel	stainless steel
Presence sensor located on the lid	•	•	•	•	•
Warm air drying option	•	•	•	•	•
Heated seat	•	•	•	•	•
Toilet backlight	•	•	•	•	•
Automatic nozzle cleaning	•	•	•	•	•
Automatic replacement of the washing water with fresh	•	•	•	•	•
Inlet water filtration	•	•	•	•	•
Descaling function	ceramic valve	ceramic valve	ceramic valve	ceramic valve	ceramic valve
Remote control control (access to all functions)		•	•		•
Side button panel control (simplified version with access to selected functions)		Front wash, Rear wash, Drying, Stop, right-hand operation	Front wash, Rear wash, Drying, Stop, right-hand operation		Front wash, Rear wash, Drying, right-hand operation

Side button panel control (extended version with access to all functions)	●			●	
Energy saving mode	●	●	●	●	●
Seat and toilet lid descent buffer	●	●	●	●	●
Heating system with instantaneous water heating and access to unlimited hot water	●	●	●	●	●
Option to adjust the water temperature	●	●	●	●	●
Option to adjust the temperature of the toilet seat	●	●	●	●	●
Option to adjust the dryer power	●	●	●	●	●
Option to adjust the position of the nozzle deflection		●	●	●	●
Option to adjust the water pressure	●	●	●	●	●
Automatic mode	●	●	●	●	●
Child mode	●	●	●	●	●
Programming the settings for users	1 person	1 person	1 person	1 person	1 person
The board and the antibacterial cover are made made of durable ABS plastic	●	●	●	●	●
Top quality Japanese main capacitors	●	●	●	●	●
The net weight of the product	4,5 kg	4,5 kg	4,5 kg	4,5 kg	4,5 kg
The external dimensions of the product (including side panels)	480 x 455 x 145 mm	480 x 410 x 145 mm	510 x 385 x 145 mm	510 x 455 x 145 mm	510 x 410 x 145 mm
Internal dimensions of the toilet seat opening (designated in extreme places)	280 x 203 mm	280 x 203 mm	292 x 203 mm	297 x 203 mm	297 x 203 mm
The location of the connection to the water supply (directions determined on the basis of the above photos)	on the right side	on the right side	on the left side	on the left side	on the left side
Electricity connection location	on the rear right	on the rear right	on the rear left side	on the back in the middle	on the back in the middle
Required inlet water pressure	0.08 ~ 0.75MPa (0.8 ~ 7.5Bar)	0.08 ~ 0.75MPa (0.8 ~ 7.5Bar)	0.08 ~ 0.75MPa (0.8 ~ 7.5Bar)	0.08 ~ 0.75MPa (0.8 ~ 7.5Bar)	0.08 ~ 0.75MPa (0.8 ~ 7.5Bar)
Maximum current consumption during operation	1450W	1450W	1450W	1450W	1450W