

					
	1 product group Topaz 4701FW	2 product group Royal i6-S	3 product group Classic 4050FW, Deluxe A 4020FW, Deluxe B 4020FB, Black Pearl 4030F	4 product group Superior 7012B, Supreme 7019B	5 product group Luxurious 1013BQ
Toilet bowl type	wall-hung bowl connected to the rack with the tank	wall-hung bowl connected to the rack with the tank	wall-hung bowl connected to the rack with the tank	wall-hung bowl connected to the rack with the tank	floor standing bowl connected directly to the drain
Rear washing (spot water jet)	•	•	•	•	•
Front washing (diffused water jet)	•	•	•	•	•
Washing in a mobile mode (massage)	•	•	•	•	•
Antibacterial washing nozzle	plastic, new generation curved nozzle, easily removable for cleaning	plastic, new generation curved nozzle, easily removable for cleaning	plastic, new generation curved nozzle, easily removable for cleaning	plastic, new generation curved nozzle	stainless steel
Presence sensor located on the lid	•	•	•	•	•
Presence sensor located at the bottom of the toilet bowl				foot sensor	foot sensor
Warm air drying option	•	•	•	•	•
Heated seat	•	•	•	•	•
Toilet backlight	•	•	•	•	•
Automatic water flushing	only when using the dedicated MAJOR & MAKER water tank model	only when using the dedicated MAJOR & MAKER water tank model	only when using the dedicated MAJOR & MAKER water tank model	no possibility	•
Water flushing method	water taken from the tank after pressing the flush button	water taken from the tank after pressing the flush button	water taken from the tank after pressing the flush button	water taken from the tank after pressing the flush button	water taken directly from the source automatically or manually
Automatic nozzle cleaning	•	•	•	•	•
Automatic replacement of the washing water with fresh	•	•	•	•	•
Automatic washing of the inside of the toilet bowl in the process of flushing the water	•	•	•	•	•
Inlet water filtration	•	•	•	•	•
Descaling function	solenoid reducing valve	solenoid reducing valve	dedicated descaling program	dedicated descaling program	ceramic valve
Absorber of unpleasant odors	•	•	•	•	•
Remote control	•	•	•	•	•
Button panel on the side	push button panel flush with the device	knob with buttons	push button panel flush with the device, knob	push button panel flush with the device	single button
Energy saving mode	built-in intelligent energy management system	built-in intelligent energy management system	built-in intelligent energy management system	possible activation of the ECO mode	possible activation of the ECO mode
A rimless bowl	rimless	rimless	rimless	semi-rimless	semi-rimless
Toilet bowl pre-wet function (reduced susceptibility to dirt)			•		•
Cover and lid closing and opening options	manually, fall buffer	manually, fall buffer	manually, fall buffer	automatic movement, remote control, foot sensor	automatic mechanism, remote control, soft closing, foot sensor
Automatic closing of lid and cover				automatic shutdown after 2 minutes of inactivity	automatic close after 2 minutes of inactivity
Heating system with instantaneous water heating and access to unlimited hot water	•	•	•	•	•
Option to adjust the water temperature	•	•	•	•	•
Option to adjust the temperature of the toilet seat	•	•	•	•	•
Option to adjust the dryer power	•	•	•	•	•
Option to adjust the position of the nozzle deflection	•	•	•	•	•
Option to adjust the water pressure	•	•	•	•	•
Automatic mode				•	•
Child mode				•	•
Programming the settings for users	1 user	1 user	1 user	1 user	1 user
Panel with display and control LEDs on the top body of the product			•	•	•
Anti-bacterial seat and cover made of durable ABS or duroplast	•	•	•	•	•
A toilet bowl made of first-class ceramics	•	•	•	•	•
Top quality Japanese main capacitors	•	•	•	•	•
The net weight of the product	25 kg	28 kg	29.5 kg	28 kg	43,7 kg
Overall dimensions of the product	560 x 370 x 403 mm	599 x 385 x 400 mm	599 x 385 x 400 mm	598 x 380 x 332 mm	670 x 418 x 480 mm
Water consumption during flushing	2/4 or 3/6 liters depending on the configuration of the frame and button	2/4 or 3/6 liters depending on the configuration of the frame and button	2/4 or 3/6 liters depending on the configuration of the frame and button	2/4 or 3/6 liters depending on the configuration of the frame and button	4,5 liters
Required inlet water pressure	0.075 ~ 0.8MPa (0.75 ~ 8.0Bar)	0.075 ~ 0.8MPa (0.75 ~ 8.0Bar)	0.07 ~ 0.75MPa (0.7 ~ 7.5Bar)	0.15 ~ 0.75MPa (1.5 ~ 7.5Bar)	the flush takes 4.5 liters of water in 14 seconds
Maximum current consumption during operation	1400W	1600W	1400W	1600W	1800W
Type of sewer drain	horizontal	horizontal	horizontal	horizontal	horizontal